



Portable SSDs

ESD240C Portable SSD

Transcend's ESD240C is a portable solid state drive featuring a sturdy metallic case in a silver hue, a USB 3.1 Gen 2 interface for unmatched transfer rates, and a USB Type-C port. In addition, the ESD240C is rigorously tested, offering optimum shock-resistant qualities.



Transfer in a blink of an eye

The ESD240C is equipped with the USB 3.1 Gen 2 interface with the support of UASP (USB Attached SCSI Protocol), providing transfer speeds of up to 520MB/s.



A tailor-made design

The ESD240C features a lightweight aluminum construction and optimum shock-resistant qualities, making it both portable and durable. The sturdy texture and silver hue complement the minimalist style of your PC.



Expand storage in a flash

The ESD240C provides up to 480GB of storage capacity, ensuring you have plenty of space for backups, as well as storing your high-resolution images, 4K videos, and other media files!



Portable SSDs

ESD240C Portable SSD

Features

- USB 3.1 Gen 2 interface with the support of UASP (USB Attached SCSI Protocol)
- 3D NAND flash
- Sturdy metallic case in a silver hue
- USB Type-C and USB Type-C to Type-A cable included



Transcend Elite

Transcend Elite is a data management software for external hard drives, USB flash drives and portable SSD products.

Specifications

Appearance

Dimensions	81.4 mm x 33.6 mm x 7.5 mm (3.21" x 1.32" x 0.30")
Weight	33 g (1.16 oz)
Color	Silver

Interface

USB Type	USB Type C to USB Type A / USB Type C to USB Type C
Connection Interface	USB 3.1 Gen 2

Storage

Flash Type	3D NAND flash
Capacity	120 GB / 240 GB / 480 GB

Operating Environment

Operating Temperature	0°C (32°F) ~ 60°C (140°F)
Operating Voltage	5V

Performance

Read Speed (Max.)	up to 520 MB/s
Write Speed (Max.)	up to 460 MB/s

Warranty

Certificate	CE / FCC / BSMI / KC / RCM / EAC
Warranty	Three-year Limited Warranty

Ordering Information

120GB	TS120GESD240C
240GB	TS240GESD240C
480GB	TS480GESD240C

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment.